

Liberty Platinum Sound System

MADE IN USA



SIX YEAR WARRANTY

Technical Specifications

The Liberty Platinum is the fourth generation in the twenty year history of the Liberty. It just keeps getting better with advances in audio technology, music players, LED development and speaker performance.

The Liberty Platinum maintains the integrity of the very first Anchor product - *Intelligible Sound, Reliable Performance and Simplicity of Use.*



Features

Reach Crowds of 2,000+

AC Mode = 125W / DC Mode = 100W

Single or Dual Built-in UHF Wireless with 16 User Selectable Channels

Optional Built-In MP3 Player Accepts SD Card, USB Flash Drive or 3.5mm input for iPod

Optional Built-In CD Player

USB Port for Charging MP3/iPod®

"Voice Over" Music Ducking Feature

Two Universal Microphone Input Jacks

Recessed Back Panel Protects Knobs and Ports

True AC/DC - 110/220V Power Supply

Ceramic Compression Driver

10" Neodymium Woofer

Proprietary Class D Amplifier

User Replaceable Batteries

Charging LED Bar Indicator

Operates 6-8 hours on a Single Charge

Speaker Out to Power Companion Speaker

LIBERTY MODELS

LIB-7500	AC/DC powered sound system
LIB-7500U1	One built-in wireless receiver
LIB-7500U2	Two built-in wireless receivers
LIB-7500M	Built-in MP3 player
LIB-7500MU1	Built-in MP3 player & one built-in wireless receiver
LIB-7500MU2	Built-in MP3 player & two built-in wireless receivers
LIB-7500C	Built-in CD player
LIB-7500CU1	Built-in CD player & one built-in wireless receiver
LIB-7500CU2	Built-in CD player & two built-in wireless receivers
LIB-7501	Unpowered speaker

ACCESSORIES

MIC-90	Professional dynamic, cardioid pattern handheld microphone
NL-7500	Nylon slip cover
HC-ARMOR30	Anchor Armor hard case - Liberty
MP3-TOTE	Holds MP3 player & microphone
SOFT-7500	Soft rolling case

UHF WIRELESS



WH-6000	Wireless handheld microphone transmitter
WB-6000	Wireless body-pack transmitter (requires handsfree microphone)
Microphone options include: Over-the-Ear/EM-TA4F, Lapel/LM-60, Collar/CM-60, Headband/HBMTA4F	

TECHNICAL SPECIFICATIONS

Rated Power Output	125 watts AC / 100 watts DC
Max SPL @ Rated Power	110 dB
Battery	Two 12 V rechargeable, 9.0 AH Full recharge: approx 7 hrs
Frequency Response	60 Hz - 15 kHz ± 3dB
Line Output (post fader)	isolated, 600 Ω, 1/4" phone
AC Power Reqs.	100 - 240 VAC, 50/60 Hz, 300W max
DC Out	12V 500mA
USB	5V 500mA
Dimensions (HWD)	22" x 14" x 11.5" (56 x 35.6 x 29.2 cm)
Weight	38 lbs / 17 Kg

Mic Inputs:	Lo-Z (1 KΩ), balanced, XLR 12 VDC condenser mic (phantom) power Hi-Z (10 KΩ), unbalanced, 1/4" phone Hi-Z (10 KΩ), unbalanced, 1/8" stereo, 1/4" phone unbalanced, stereo RCA
Line In/Out	
Sensitivity For Rated Output	
Lo-Z Microphone	-52 dBV (2.5 mVrms)
Hi-Z Microphone	-43 dBV (7.5 mVrms)
Auxiliary (line)	-14 dBV (200 mVrms)
Phantom Power	36V
Speaker Out	4-pole Neutrik Speakon® jack

(Features & Specifications Subject to Change Without Notice)



(LIB-7500MU2 with MP3 player)



(LIB-7500CU2 with CD player)



Anchor Audio, Inc.

Portable Sound Systems • Carlsbad, California

800.262.4671

www.anchoraudio.com

S-L/0910